

Technical data (extract)

* EPREL data base is available at <https://eprel.ec.europa.eu/screen/product/lightsources/xxxxxxx>
(where the xxxxxx have to be substituted by the reference number given in the last coloumn)

Products with 3 years or with extended 5 years warranty	Power (W)	Lum. total luminous flux emitted (lm)		Lum. efficacy (lm/W)		CCT (Kelvin)	CRI	Lifetime L70B50 (Ta=35°C)	Lifetime L80B10 (Ta=35°C)	A (mm)	B (mm)	Weight (kg)	EEI	Light source* (reference)
		PMMA	PC	PMMA	PC									
Lumnium3 Farmer HV														
771 2 ft (600 mm)	14	1900	n.a.	136	n.a.	4000	>80	50 000 h	50 000 h	669	360	1,2	D	696329
771 4ft (1200mm)	23	3800	n.a.	164	n.a.	4000	>80	50 000 h	50 000 h	1277	700	2	D	696329
771 5ft (1500mm)	33	5000	n.a.	152	n.a.	4000	>80	50 000 h	50 000 h	1577	1000	2,2	D	696329
771 5ft (2x1500mm)**	43	6600	n.a.	154	n.a.	4000	>80	50 000 h	40 000 h	1577	1000	2,2	D	696329
Lumnium5 Farmer HV														
771 2 ft (600 mm)	14	1900	n.a.	136	n.a.	4000	>80	50 000 h	50 000 h	669	360	1,2	D	696329
771 4ft (1200mm)	23	3800	n.a.	164	n.a.	4000	>80	50 000 h	50 000 h	1277	700	2	D	696329
771 5ft (1500mm)	33	5000	n.a.	152	n.a.	4000	>80	50 000 h	50 000 h	1577	1000	2,2	D	696329
771 5ft (2x1500mm)**	43	6600	n.a.	154	n.a.	4000	>80	50 000 h	40 000 h	1577	1000	2,2	D	696329

** The LED strips are placed in one line in a twin (wider) housing.

Other colour temperatures available on request