

Technical data (extract)

* EPREL data base is available at <https://eprel.ec.europa.eu/screen/product/lightsources/xxxxxxx>
(where the xxxxxx have to be substituted by the reference number given in the last coloumn)

Products with 5 years warranty	Power (W)	Lum. total luminous flux emitted (lm)		Lum. efficacy (lm/W)		CCT (Kelvin)	CRI	Lifetime L70B50 (Ta=+50°C)	Lifetime L80B10 (Ta=+50°C)	A (mm)	B (mm)	Weight (kg)	EEI	Light source* (reference)
		PMMA	PC	PMMA	PC									
Philips Fortimo LED Strip LV														
771 4ft (1200mm)	26	n.a.	3 400	n.a.	132	4000	>80	>70 000 h	>50 000 h	1277	700	2,2	C	778351
771 5ft (1500mm)	31	n.a.	4 200	n.a.	135	4000	>80	>70 000 h	>50 000 h	1577	1000	2,5	C	778365
771 5ft (2x1500mm)**	39	n.a.	5 200	n.a.	134	4000	>80	>70 000 h	>50 000 h	1577	1000	2,7	C	778365
Philips Fortimo LED Strip HV6														
771 4ft (2x1200mm)**	59	n.a.	8 100	n.a.	137	4000	>80	>50 000 h	>50 000 h	1277	700	2,65	C	893529
771 5ft (2x1500mm)**	70	n.a.	9 900	n.a.	141	4000	>80	>50 000 h	>50 000 h	1577	1000	3	C	893525 893529

** The LED strips are placed in one line in a twin (wider) housing.

Other colour temperatures available on request