

## Technical data (extract)

\* EPREL data base is available at <https://eprel.ec.europa.eu/screen/product/lightsources/xxxxxxx>  
(where the xxxxxx have to be substituted by the reference number given in the last coloumn)

Products with 5 years or optionally with 3 years warranty	Power (W)	Lum. total luminous flux emitted (lm)		Lum. efficacy (lm/W)		CCT (Kelvin)	CRI	Lifetime L70B50 (Ta=35°C)	Lifetime L80B10 (Ta=35°C)	A (mm)	B (mm)	Weight (kg)	EEI	Light source* (reference)
		PMMA	PC	PMMA	PC									
<b>Lumnium EU 130 SO with Osram driver</b>														
792 2ft (600mm)	24	n.a.	3000	n.a.	125	4000	>80	>72 000 h	>50 000 h	610	230	0,91	D	1059419
792 4ft (1200mm)	25	n.a.	3200	n.a.	128	4000	>80	>72 000 h	>50 000 h	1180	860	1,49	D	802364
792 5ft (1500mm)	30	n.a.	4000	n.a.	133	4000	>80	>72 000 h	>50 000 h	1480	1160	1,79	D	734821
792 4ft (1200mm)	38	n.a.	4900	n.a.	128	4000	>80	>72 000 h	>50 000 h	1180	860	1,49	D	734862
792 5ft (1500mm)	50	n.a.	6500	n.a.	130	4000	>80	>72 000 h	>50 000 h	1480	1160	1,79	D	734813
<b>Lumnium EU PRO 160 SO with Osram driver</b>														
792 4ft (1200mm)	22	n.a.	3200	n.a.	145	4000	>80	>72 000 h	>50 000 h	1180	860	1,49	C	803878
792 5ft (1500mm)	27	n.a.	4000	n.a.	148	4000	>80	>72 000 h	>50 000 h	1480	1160	1,79	C	734800
792 4ft (1200mm)	31	n.a.	4700	n.a.	151	4000	>80	>72 000 h	>50 000 h	1180	860	1,49	C	803933
792 5ft (1500mm)	41	n.a.	6400	n.a.	156	4000	>80	>72 000 h	>50 000 h	1480	1160	1,79	C	734760
<b>Osram Basic Linear G3</b>														
792 2ft (600mm)	21	n.a.	2500	n.a.	119	4000	>80	>50 000	>43 000	610	230	0,9	D	892178
792 4ft (1200mm)	23	n.a.	3000	n.a.	131	4000	>80	>50 000	>50 000	1180	860	1,45	D	892186
792 5ft (1500mm)	28	n.a.	3800	n.a.	138	4000	>80	>50 000	>50 000	1480	1160	1,72	D	892176 892186
792 4ft (1200mm)	39	n.a.	5300	n.a.	136	4000	>80	>50 000	>41 000	1180	860	1,45	D	892188
792 5ft (1500mm)	47	n.a.	6400	n.a.	135	4000	>80	>50 000	>41 000	1480	1160	1,72	D	892178 892188