

Technical data (extract)

PMMA Type	Power (W)	Warranty (years)	Luminare total luminous flux - emitted (lm)	Lum. efficacy (lm/W)	Correlated colour temp (Kelvin)	CRI	Lifetime L70B50 (Ta=35°C)	Lifetime L80B10 (Ta=35°C)	A (mm)	B (mm)	Weight (kg)
Lumnium EU 130 with Osram driver											
870 4ft (1200mm)	37	5 years	5400	146	4000	>80	> 72 000 h *	> 50 000 h *	1174	700 +/- 76	2
870 5ft (1500mm)	51	5 years	7300	143	4000	>80	> 72 000 h *	> 50 000 h *	1454	1000 +/- 76	2,2
Lumnium EU PRO 160 with Osram driver											
870 4ft (1200mm)	32	5 years	5200	163	4000	>80	> 72 000 h	> 50 000 h	1174	700 +/- 76	2
870 5ft (1500mm)	44	5 years	7300	166	4000	>80	> 72 000 h	> 50 000 h	1454	1000 +/- 76	2,2
Lumnium EU PRO 140 HF with Philips driver											
870 4ft (1200mm)	61	5 years	8600	141	4000	>80	> 72 000 h	> 50 000 h	1174	700 +/- 76	2
870 5ft (1500mm)	77	5 years	10900	142	4000	>80	> 72 000 h	> 50 000 h	1454	1000 +/- 76	2,2
Philips Fortimo HV6											
870 4ft (1200mm)	60	5 years	9100	152	4000	>80	> 100 000 h	> 64 000 h	1174	700 +/- 76	2
870 5ft (1500mm)	75	5 years	11400	152	4000	>80	> 100 000 h	> 64 000 h	1454	1000 +/- 76	2,2
870 4ft (1200mm)	74	5 years	11500	155	4000	>80	> 100 000 h	> 64 000 h	1174	700 +/- 76	2
870 5ft (1500mm)	92	5 years	14500	158	4000	>80	> 100 000 h	> 64 000 h	1454	1000 +/- 76	2,2

* The application of through-wiring may influence the Ta. max.

with DIP Switch PMMA Type	Power (W)	Warranty (years)	Luminare total luminous flux - emitted (lm)	Lum. efficacy (lm/W)	Correlated colour temp (Kelvin)	CRI	Lifetime L70B50 (Ta=35°C)	Lifetime L80B10 (Ta=35°C)	A (mm)	B (mm)	Weight (kg)
Lumnium EU 160 with Osram driver											
870 4ft (1200mm)	19	5 years	3100	165	4000	>80	> 72 000 h	> 50 000 h	1185	700±78	2
	23		3800								
	27		4700								
	32		5200								
870 5ft (1500mm)	25	5 years	4200	165	4000	>80	> 72 000 h	> 50 000 h	1477	1000±78	2,2
	32		5400								
	38		6400								
	44		7500								