

Technical data (extract)

PMMA Type	Power (W)	Warranty (years)	Luminare total luminous flux - emitted (lm)	Lum. efficacy (lm/W)	Correlated colour temp (Kelvin)	CRI	Lifetime L70B50 (Ta=35°C)	Lifetime L80B10 (Ta=35°C)	A (mm)	B (mm)	Weight (kg)
-----------	-----------	------------------	---	----------------------	---------------------------------	-----	---------------------------	---------------------------	--------	--------	-------------

Lumnium EU 130 with Osram driver

872 4ft (1200mm)	36	5 years	5300	136	4000	>80	> 72 000 h	> 50 000 h	1185	700±78	1,5
872 5ft (1500mm)	50	5 years	7000	137	4000	>80	> 72 000 h	> 50 000 h	1477	1000±78	1,8

Lumnium EU PRO 160 with Osram driver

872 4ft (1200mm)	31	5 years	5000	161	4000	>80	> 72 000 h	> 50 000 h	1185	700±78	1,5
872 5ft (1500mm)	41	5 years	6800	165	4000	>80	> 72 000 h	> 50 000 h	1477	1000±78	1,8

Osram Basic Linear G3

872 4ft (1200mm)	39	5 years	5400	140	4000	>80	50.000 h	41.000 h	1185	700±78	1,5
872 5ft (1500mm)	47	5 years	6900	145	4000	>80	50.000 h	41.000 h	1477	1000±78	1,8

with DIP Switch PMMA Type	Power (W)	Warranty (years)	Luminare total luminous flux - emitted (lm)	Lum. efficacy (lm/W)	Correlated colour temp (Kelvin)	CRI	Lifetime L70B50 (Ta=35°C)	Lifetime L80B10 (Ta=35°C)	A (mm)	B (mm)	Weight (kg)
------------------------------	--------------	---------------------	---	----------------------------	---------------------------------------	-----	---------------------------------	---------------------------------	-----------	-----------	----------------

Lumnium EU 130 HO with Osram driver

872 4ft (1200mm)	23	5 years	3400	136	4000	>80	> 72 000 h	> 50 000 h	1185	700±78	1,5
	28		4100								
	34		4800								
	39		5300								
872 5ft (1500mm)	30	5 years	4500	137	4000	>80	> 72 000 h	> 50 000 h	1477	1000±78	1,8
	37		5500								
	44		6400								
	51		7000								