

Technical data 870-NB GRP

Order code PC	Products with a 5-year warranty	Power (W)	Luminare total luminous flux - emitted (lm)	Efficacy (lm/W)	CRI	*Lifetime L80B10 (Ta=50°C)	A (mm)	B (mm)	Weight (kg)	EEI
TCI LED module or equivalent alternative with DIP switch driver (CCT: 4000K, on request other CCTs are available)										
V87014P6004A00D	4ft (1200mm)	74	11600	147	>80	> 64 000 h	1174	700±76	2,1	C
V87015P6004A00D	5ft (1500mm)	92	14500	148	>80	> 64 000 h	1454	980±76	2,3	C
DALI										
V87014P6004C00D	4ft (1200mm)	74	11600	147	>80	> 64 000 h	1174	700±76	2,1	C
V87015P6004C00D	5ft (1500mm)	92	14500	148	>80	> 64 000 h	1454	980±76	2,3	C

Order code PMMA	Products with a 5-year warranty	Power (W)	Luminare total luminous flux - emitted (lm)	Efficacy (lm/W)	CRI	*Lifetime L80B10 (Ta=50°C)	A (mm)	B (mm)	Weight (kg)	EEI
TCI LED module or equivalent alternative with DIP switch driver (CCT: 4000K, on request other CCTs are available)										
V87014P6004A00C	4ft (1200mm)	74	11600	145	>80	> 64 000 h	1174	700±76	2,1	C
V87015P6004A00C	5ft (1500mm)	92	14500	146	>80	> 64 000 h	1454	980±76	2,3	C
DALI										
V87014P6004C00C	4ft (1200mm)	74	11600	145	>80	> 64 000 h	1174	700±76	2,1	C
V87015P6004C00C	5ft (1500mm)	92	14500	146	>80	> 64 000 h	1454	980±76	2,3	C

* For more detailed lifetime data and ambient temperature, see the datasheet.
The application of through wiring may change the maximum allowed ambient temperature (Ta max.)

Technical data 870-NB PC

Order code PC	Products with a 5-year warranty	Power (W)	Luminare total luminous flux - emitted (lm)	Efficacy (lm/W)	CRI	*Lifetime L80B10 (Ta=50°C)	A (mm)	B (mm)	Weight (kg)	EEI
TCI LED module or equivalent alternative with DIP switch driver (CCT: 4000K, on request other CCTs are available)										
V87014P6004A00F	4ft (1200mm)	74	11600	147	>80	> 64 000 h	1174	700±76	2,1	C
V87015P6004A00F	5ft (1500mm)	92	14500	148	>80	> 64 000 h	1454	980±76	2,3	C
DALI										
V87014P6004C00F	4ft (1200mm)	74	11600	147	>80	> 64 000 h	1174	700±76	2,1	C
V87015P6004C00F	5ft (1500mm)	92	14500	148	>80	> 64 000 h	1454	980±76	2,3	C

Order code PMMA	Products with a 5-year warranty	Power (W)	Luminare total luminous flux - emitted (lm)	Efficacy (lm/W)	CRI	*Lifetime L80B10 (Ta=50°C)	A (mm)	B (mm)	Weight (kg)	EEI
TCI LED module or equivalent alternative with DIP switch driver (CCT: 4000K, on request other CCTs are available)										
V87014P6004A00E	4ft (1200mm)	74	11600	145	>80	> 64 000 h	1174	700±76	2,1	C
V87015P6004A00E	5ft (1500mm)	92	14500	146	>80	> 64 000 h	1454	980±76	2,3	C
DALI										
V87014P6004C00E	4ft (1200mm)	74	11600	145	>80	> 64 000 h	1174	700±76	2,1	C
V87015P6004C00E	5ft (1500mm)	92	14500	146	>80	> 64 000 h	1454	980±76	2,3	C

* For more detailed lifetime data and ambient temperature, see the datasheet.
The application of through wiring may change the maximum allowed ambient temperature (Ta max.)